# HANGZHOU HANHAO CHEMICAL CO., LTD

Plant: Jiangdong Development Zone, Great Jiangdong District, Hangzhou China
Office: 2103 Bldg1, Dacheng Plaza, Shixin Road, Xiaoshan, Hangzhou, China
Tel:+86-571-82502631/82551631
Fax:+86-571-82722631

## TECHNICAL DATA SHEET

#### **Product Description:**

Color Index:	Solvent Yellow 93
C.I.No.	48160
CAS No.	4702 <mark>-90-3</mark>
EC NO.	225- <mark>184-</mark> 1
Chemical Family	Pyrazolone Series
Chemical Formula	$\mathbf{C}_{21}\mathbf{H}_{18}\mathbf{N}_{4}\mathbf{O}_{2}$

## **Technical Properties:**

The product is greenish yellow oil solvent dye. It is of high heat resistant ability, good light fastness and strong dyeing power.

## Application: (" $\bigstar$ " Superior, " $\bigcirc$ " Applicable, " $\triangle$ " Not recommend

PS	HIPS	ABS	PC	RPVC	PMMA	S <mark>AN</mark>	AS	PA6	РЕТ
☆	0	ΔO	0	☆	☆	0	0	$\triangle$	0

Also use in oil products, wax, fat, printing ink and etc.

#### **Physical Properties**

Density(g/cm3)	Melting	Light fastness	Recommended Dosage	
	Point(°C)	(in PS)	Transparent Nontranspar	
1.32	181	6-7	0.03	0.1

Light Fastness: Consist of 1<sup>st</sup> to 8<sup>th</sup> grade, and the 8<sup>th</sup> grade is superior, the 1<sup>st</sup> grade is bad.

#### The heat resistance in PS can reach to 300℃

Degree of pigmentation: 0.05% dyes+0.1% titanium dioxide R

#### Solvent yellow 93 solubility in organic solvent at 20°C(g/l)

Acetone	Butyl Acetate	Methylbenzene	Dichloromethane	Ethylalcohol
8	10	25	190	1

Note: The above information is provided as guidelines for your reference only. The accurate effects should base on the test results in laboratory.